

MDL-III-520L/1~50mW



### GREEN DIODE LASER AT 520 nm

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are widely used in laser projection, laser shows, biomedical applications, holography, metrology, etc.



### SPECIFICATIONS

Wavelength (nm)	520±5
Operating mode	CW
Output power (mW)	>1, 2, 3, ..., 50
Power stability (rms, over 4 hours)	<1%, <2%, <3% (<0.5%, optional)
Transverse mode	Near TEM <sub>00</sub>
Beam diameter at the aperture ((1/e <sup>2</sup> ),mm)	~3.0
Beam divergence, full angle (mrad)	<1.0
Polarization ratio	>50:1 (>100:1, optional) Horizontal±5 degree (Vertical Optional)
Warm-up time (minutes)	<5
Pointing stability after warm-up (mrad)	<0.05
Beam height from base plate (mm)	24.8
Operating temperature (°C)	10~35
Power supply	85-264VAC
	100-240VAC
TTL / Analog modulation	PSU-III-LED/ PSU-III-FDA (Frequency for 1Hz-30kHz) PSU-A-D (Frequency for 30kHz -100kHz)
Expected lifetime (hours)	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional 10000
Warranty	1 year



MDL-III-520L	PSU-III-LED	PSU-III-FDA	PSU-A-D
<p>143.5(L)×73(W)×46.2(H) mm<sup>3</sup>, 0.7kg</p>	<p>188.6 (L) ×155(W) ×92 (H) mm<sup>3</sup>, 1.5kg</p>	<p>171(L) ×130(W) ×62.2 (H) mm<sup>3</sup>, 1.2kg</p>	<p>162(L) ×144(W) ×70 (H) mm<sup>3</sup>, 1.0kg</p>