Opto Engine LLC

Data sheet

Rev. 1505

PGL-H-1064/1~1000mW

HIGH POWER INFRARED LASER MODULE AT 1064nm

PGL-H high power infrared laser module at 1064nm is made features of small size, high output power, long lifetime, which made it widely used in collimation, laser medical treatment, scientific experiment, optical instrument and so on.



SPECIFICATIONS

Model	PGL-H-1064		
Wavelength (nm)	1064±1		
Output power (mW)	>1, 10, 15, , 1000		
Transverse mode	TEM_{00}		
Operating mode	CW		
Beam divergence, full angle (mrad)	<15		
Beam diameter at the aperture (mm)	~0.3		
Power stability (rms)	<10%, over 4 hours at constant temperature after warm up		
	<20%, over operating temperature range		
Warm-up time (minutes)	<10		
Operating temperature (°C)	15~30		
Power supply	3V PCB	5V PCB	
TTL modulation	Optional, 1Hz-1KHz, 1KHz-10KHz, or higher on request		
Expected lifetime (hours)	5000		
Warranty	6 months		





PGL-H-1064	Dimensions	3VPCB	5VPCB
Φ26×55.5(L) mm³, 0.3 kg	55.50	Φ26×15(H) mm ³	56×47×30(H) mm ³