

MDL-H-808/3000~6000mW


INFRARED DIODE LASER AT 808nm

Diode infrared laser module at 808nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	808 ± 3		
Output power (mW)	>3000, 3100, 3200, ..., 6000		
Transverse mode	Near TE ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<5		
M ² factor	<20		
Beam divergence, full angle (mrad)	<3.0		
Beam diameter at the aperture (mm)	5~8		
Beam height from base plate (mm)	29		
Polarization ratio	>50:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
Expected lifetime (hours)	10000		
Warranty period	1 year		



MxL-H-808	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
<p>155(L)×77(W)×60(H) mm³, 0.9 kg</p>	<p>240 (L) ×146(W) ×108 (H) mm³, 2.6 kg</p>	<p>238 (L) ×146(W) ×102 (H) mm³, 2.3 kg</p>	<p>238 (L) ×146(W) ×94 (H) mm³, 2.2 kg</p>