

MGL-N-532/3000~5000mW

LD PUMPED ALL-SOLID-STATE GREEN LASER





All solid state 532nm green laser is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, laser display, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	532 ± 1		
Output power (mW)	>3000, 3500, 4000, ..., 5000		
Transverse mode	Near TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%, <10%		
Warm-up time (minutes)	<10		
M ² factor	3.0~5.0 (<2.0 on request)		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at the aperture (mm)	~3.0		
Beam height from base plate (mm)	68.2		
Polarization ratio	>100:1		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
TTL modulation/ Analog modulation	Optional, 2kHz or higher (others on request, up to 30kHz)		
Expected lifetime (hours)	10000		
Warranty period	1 year		



MGL-N-532	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
 <p>235(L)×99(W)×94(H) mm³, 2.6 kg</p>	 <p>240 (L) ×146(W) ×108 (H) mm³, 2.6 kg</p>	 <p>238 (L) ×146(W) ×102 (H) mm³, 2.3 kg</p>	 <p>215 (L) ×129 (W) ×122 (H) mm³, 2.145 kg</p>
