

MGL-N-561/200~500mW

LD PUMPED ALL-SOLID-STATE YELLOW LASER AT 561nm





All solid state 561 nm yellow green laser is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in laser medical treatment, scientific experiment, optical instrument, etc.



SPECIFICATIONS

Wavelength (nm)	561 ± 1		
Output power (mW)	>200, 300, 400, ..., 500		
Transverse mode	Near TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<10%		
Warm-up time (minutes)	<10		
M ² factor	<3.0		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at the aperture (mm)	~4.0		
Beam height from base plate (mm)	68.2		
Polarization ratio	>100:1		
Operating temperature (°C)	10~35		
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
TTL modulation/ Analog modulation	Optional, 2kHz or higher (others on request, up to 10kHz)		
Expected lifetime (hours)	10000		
Warranty period	1 year		



MxL-N-561	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
			
235(L)×99(W)×94(H) mm ³ , 2.6 kg	240 (L) ×146(W) ×108 (H) mm ³ , 2.6 kg	238 (L) ×146(W) ×102 (H) mm ³ , 2.3 kg	215 (L) ×129 (W) ×122 (H) mm ³ , 2.145 kg
