

MIL-III-1342/1~1000mW


LD PUMPED ALL-SOLID-STATE INFRARED LASER AT 1342nm

All solid state infrared laser is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, measurement, optical instrument, optical sensor, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	1342±1		
Output power (mW)	>1, 5, 10, 20, ... , 1000		
Laser crystal	Nd:YVO ₄		
Transverse mode	TEM ₀₀		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Warm-up time (minutes)	<10		
M ² factor	<1.2		
Beam divergence, full angle (mrad)	<1.5		
Beam diameter at the aperture (mm)	~2.0		
Beam height from base plate (mm)	24.8		
Polarization ratio	>100:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
TTL / Analog modulation	Optional, 2kHz or higher (on request, up to 30kHz)		
Expected lifetime (hours)	10000		



MxL-III-1342	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
<p>140.8(L)×73(W)×46.2(H) mm³, 0.6kg</p>	<p>154 (L) ×155(W) ×95 (H) mm³, 1.5kg</p>	<p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>	<p>100 (L) ×60(W) ×56 (H) mm³, 0.2kg</p>