

MLL-III-940/1~1500mW

### LOW NOISE INFRARED DIODE LASER AT 940 nm





Low noise diode infrared laser module at 940 nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in measurement, communication, spectrum analysis, etc.



### SPECIFICATIONS

Wavelength (nm)	940±5		
Output power (mW)	>1, 100, 200, 300, ..., 1500		
Transverse mode	Near TE <sub>00</sub>		
Operating mode	CW		
Power stability (rms, over 4 hours)	<1%, <3%, <5%		
Noise of amplitude(rms,1~20MHz)	<1%		
Warm-up time (minutes)	<5		
M <sup>2</sup> factor	<20		
Beam divergence, full angle (mrad)	<3. 0		
Dimensions of beam at the aperture (mm)	~5×8		
Beam height from base plate (mm)	24. 8		
Polarization ratio	>50:1		
Pointing stability after warm-up (mrad)	<0.05		
Operating temperature (°C)	10~35		
Power supply (90-264VAC or 5VDC)	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Expected lifetime (hours)	10000		
Warranty	1 year		



MxL-III-940	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
			
140. 8(L)×73(W)×46. 2(H) mm <sup>3</sup> , 0.6kg	154 (L) ×155(W) ×95 (H) mm <sup>3</sup> , 1.5kg	133 (L) ×130(W) ×65 (H) mm <sup>3</sup> , 1.2kg	100 (L) ×60(W) ×56 (H) mm <sup>3</sup> , 0.2kg
