

MPL-H-1064/20~100uJ/500~1500mW

### LD PUMPED ALL-SOLID-STATE Q-switched LASER

All solid state Q-switched laser at 1064nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in industry (marking on the diamond or stone), teaching of nonlinear optics, experiments of generating 355nm, or 266nm laser, fiber communication, etc.



#### SPECIFICATIONS

Wavelength (nm)	1064±1	
Operating mode	Q-switched pulsed laser	
Single pulse energy (μJ)	20~100	
Pulse duration (ns)	~10	
Peak power (W)	3000~10000	
Rep. rate (kHz)	Controllable	Specified One rep. rate, such as 1k, 2k, 3k, up to 5kHz, with stable laser pulses emitting (stable pulse energy, peak, duration and period). Different rep. rate in the range of 1Hz-5kHz can be obtained by input an external TTL signal.
	Uncontrollable	Undefined rep. rate among 5k-30kHz and unstable laser pulse emitting. Suitable for the applications only needing high peak power pulses.
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)	
Ave power stability (over 4 hours)	<1%, <3%, <5%	
Transverse mode	Near TEM <sub>00</sub>	
Warm-up time (minutes)	<10	
M <sup>2</sup> factor	<1.5	
Beam divergence, full angle (mrad)	<2.0	
Beam diameter at the aperture (mm)	~3.0	
Beam height from base plate (mm)	29	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	
Remarks	UV laser at 266nm or 355nm can be generated by MPL-H-1064 or MPL-H-532.	



MxL-H-1064	Dimensions	PSU-H-FDA	Dimensions
<p>155(L)×77(W)×60(H) mm<sup>3</sup>, 0.9 kg</p>		<p>238 (L) ×146(W) ×102 (H) mm<sup>3</sup>, 2.3 kg</p>	