

MRL-F-671/1300~2000mW

LD PUMPED ALL-SOLID-STATE RED LASER AT 671nm





All solid state 671nm Red laser is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, laser display, laser lighting show, etc.



SPECIFICATIONS

Wavelength (nm)	671±1	
Output power (mW)	>1300, 1350, 1400, ..., 1500	>1500,1600.....2000
Transverse mode	TEM ₀₀	Near TEM ₀₀
Operating mode	CW	
Power stability (rms, over 4 hours)	<3%, <5%, <10%	
Warm-up time (minutes)	<10	
M ² factor	<1.2	<2.0
Beam divergence, full angle (mrad)	<2.0	
Beam diameter at the aperture (mm)	~3.0	
Beam height from base plate (mm)	45	
Polarization ratio	>100:1	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED	PSU-H-FDA
TTL / Analog modulation	Optional, 2kHz or higher (on request, up to 30kHz)	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-F-671	PSU-H-LED	PSU-H-FDA	PSU-H-OEM
			
211.5(L)×88(W)×74(H) mm ³ , 1.6 kg	240 (L)×146(W)×108 (H) mm ³ , 2.6 kg	238 (L)×146(W)×102 (H) mm ³ , 2.3 kg	238 (L)×146(W)×94 (H) mm ³ , 2.2 kg
