

OEM-N-671/1300-3000mW

### LD PUMPED ALL-SOLID-STATE RED LASER MODULE CORE

All solid state 671 nm red laser module core is made features of ultra compact, long lifetime, low cost and easy operating. It's easy to be installed in customer's equipment.



#### SPECIFICATIONS

Wavelength (nm)	671 ± 1	
Output power (mW)	>1300, 1600, 1700, ..., 3000	
Transverse mode	Near TEM <sub>00</sub>	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%, <10%	
Warm-up time (minutes)	<15	
M <sup>2</sup> factor	<3.0	
Beam divergence, full angle (mrad)	<17	
Beam diameter at the aperture (mm)	~1.5	
Beam height from base plate (mm)	25.4 without TEC	27.4 with TEC
Operating temperature (°C)	22.5±2.5	
Operating current of Diode (A)	0-10	
Operating voltage of Diode (V)	~2.0	
Pins information	5,6,7,8: positive of diode; 12,13,14,15: negative of diode	
Power supply(two channels 6 & 12V)	PSU-OEM-N (key switch and emergency stop are available on request)	
Expected lifetime (hours)	5000	
Warranty time	The warranty is 3 months, excluding the LD failure.	
Dimension(mm)	150(L)×60(W)×44(H) without TEC, 172(L)×70(W)×50(H) with TEC	



OEM-N-671	Dimension ( Without TEC)	Dimension ( With TEC)	Accessories
	 150(L)×60(W)×44(H) without TEC	 172(L)×70(W)×50(H) with TEC	 Collimation system
PSU-OEM-N	Dimension	Power Supply Instruction	
	 170(L)×60(W)×29(H)	 V1: DC 6V 12A V2: DC 12V 8A	