

MDL-XS-420/1~120mW




### DIODE XS SERIES LASER AT 420nm

It features integrated electronics, plug and play, miniaturization, international standard interface. They are the ideal solution for a wide range of applications including life sciences, environmental monitoring, inspection and machine vision.



### SPECIFICATIONS

Central wavelength (nm)	420±10
Operating mode	CW
Output power (mW)	>1, 10, 20, ..., 120
Power stability (rms, over 4 hours)	<1%, <2%, <3%
Transverse mode	Near TEM <sub>00</sub>
Noise of amplitude(rms,20Hz~20MHz)	<1%(<0.5%, optional)
M <sup>2</sup> factor	<1.2
Beam diameter at the aperture (1/e <sup>2</sup> ,mm)	~1.2
Beam divergence, full angle (mrad)	<1.0
Polarization ratio	>50:1 (>100:1, optional) Horizontal±5 degree (Vertical Optional)
Warm-up time (minutes)	<5
Beam height from base plate (mm)	19
Operating temperature (°C)	10~35
Input voltage	+12VDC
Modulation	DMOD (TTL) up to 1MHz
	AMOD (Analog) up to 100kHz
	DMOD+ AMOD (TTL + Analog)
Expected lifetime (hours)	10000
Warranty	1 year



**Note: The laser head needs to be used on a heat sink with good heat dissipation.**

MDL-XS-420	Optional Power Supply
<p>74.4(L) × 40(W) × 40(H) mm<sup>3</sup>, 0.2kg</p>	<p>121(L) × 50(W) × 30.8(H) mm<sup>3</sup>, 0.3kg</p>