

MLL-FN-660/100~400mW




LD PUMPED ALL-SOLID-STATE LOW NOISE RED LASER AT 660nm

Low noise red laser at 660nm is made features of ultra compact, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, and scientific research etc.



SPECIFICATIONS

Wavelength (nm)	660±1	
Operating mode	CW	
Output power (mW)	>100, 110, 120, ... , 200	>200, ... , 400
Power stability (rms, over 4 hours)	<3%, <5%	3%, <5%, <10%
Transverse mode	Near TEM ₀₀	
M ² factor	<1.2	
Noise of amplitude (rms, 20Hz~20MHz)	<1%	
Beam diameter at the aperture (1/e ² , mm)	~2.0	
Beam divergence, full angle (mrad)	<1.5	
Warm-up time (minutes)	<10	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate (mm)	27.4	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-LED PSU-H-FDA	
Expected lifetime (hours)	10000	
Warranty	1 year	



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MLL-FN-660	PSU-H-LED	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm³, 2.0 kg</p>	<p>277 (L) ×145(W) ×106 (H) mm³, 2.6 kg</p>	<p>236(L) ×145(W) ×104(H) mm³, 2.3 kg</p>