

MPL-F-261/0.1~4uJ/1~10mW


LD PUMPED ALL-SOLID-STATE UV LASER

All solid state 261 nm UV laser is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in UV curing, micro-electronics, CD carving, laser medical treatment, scientific experiment, etc.



SPECIFICATIONS

Central wavelength (nm)	261±1	
Output average power (mW)	1~10	
Transverse mode	Near TEM ₀₀	
Operating mode	Frequency conversion of Q-switched pulsed laser	
Single pulse energy (μJ)	0.1~4	
Pulse duration (ns)	~4	
Peak power(W)	25~1000	
Rep. rate (kHz)	Controllable	Specified One rep. rate, such as 0.1Hz, 100 Hz, 500 Hz up to 1kHz, with stable laser pulses emitting (stable pulse energy, peak, duration and period). Different rep. rate in the range of 0.1Hz to 1kHz can be obtained by input an external TTL signal.
	Uncontrollable	Undefined rep. rate among 2kHz-3kHz and unstable laser pulse emitting. Suitable for the applications only needing high peak power pulses.
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)	
Ave power stability (over 4 hours)	<5%, <10%	
Warm-up time (minutes)	<10	
M ² factor	<1.5	
Spectral purity	>99%	
Beam parameters	Elliptical (4:1), Beam spot ~2mm	
Polarization ratio	>50:1	
Beam height from base plate (mm)	45	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	5000	
Warranty period	1 year	
Remarks	Please Note: because of the Walk-off effect of Nonlinear crystals, the beam quality of UV laser is not so good as that of 1047/523nm laser.	



MxL-F-261 (with 261/523/1047 nm laser included)	MxL-F-261 (With 261 nm laser emitting only)	PSU-H-FDA	UV prism
<p>211 (L)×88(W) ×74(H) mm³, 1.6 kg</p>	<p>245.5(L)×88(W) ×74(H) mm³, 2.0 kg</p>	<p>238 (L) ×145 (W) ×104 (H) mm³, 2.3 kg</p>	