

MPL-F-266/0.1~5uJ/1~20mW

### LD PUMPED ALL-SOLID-STATE UV LASER





All solid state 266 nm UV laser is made features of ultra compact, long lifetime, cost-effectiveness and easy operating, which is widely used in UV curing, micro-electronics, CD carving, laser medical treatment, scientific experiment, etc.



#### SPECIFICATIONS

Central wavelength (nm)	266±1	
Output average power (mW)	1~20	
Transverse mode	Near TEM <sub>00</sub>	
Operating mode	Frequency conversion of Q-switched pulsed laser	
Single pulse energy (μJ)	0.1~5	
Pulse duration (ns)	~5	
Peak power(W)	20~1000	
Rep. rate (kHz)	Controllable	Fixed rep. rate, such as 1k, 2k, 3k, 4kHz, with stable laser pulses emitting (stable pulse energy, peak, duration and period). Different rep. rate in the range of 1kHz-4kHz can be obtained by input an external TTL signal.
	Uncontrollable	Undefined rep. rate among 5k-7kHz and unstable laser pulse emitting. Suitable for the applications only needing high peak power pulses.
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)	
Ave power stability (over 4 hours)	<5%, <10%	
Warm-up time (minutes)	<10	
M <sup>2</sup> factor	<1.5	
Spectral purity	>99%	
Beam parameters	Elliptical (4:1), Beam spot ~2mm	
Polarization ratio	>100:1	
Beam height from base plate (mm)	45	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	5000	
Warranty period	1 year	
Remarks	Please Note: because of the Walk-off effect of Nonlinear crystals, the beam quality of UV laser is not so good as that of 1064/532nm laser.	



MxL-F-266 (with 266/532/1064 nm laser included)	MxL-F-266 (With 266 nm laser emitting only)		PSU-H-FDA	UV prism
 211 (L) × 88(W) × 74(H) mm <sup>3</sup> , 1.6 kg	 287(L) × 224(W) × 100.5(H) mm <sup>3</sup> , 4.2 kg	 245.5(L) × 88(W) × 74(H) mm <sup>3</sup> , 2.0 kg <i>New!</i>	 236 (L) × 145 (W) × 104 (H) mm <sup>3</sup> , 2.3 kg	